

SABIC® HDPE PCGF0863

HIGH DENSITY POLYETHYLENE

DESCRIPTION

SABIC® HDPE grades for healthcare applications are produced under controlled conditions resulting in high product quality, consistency and a high level of purity.

SABIC® HDPE PCGF0863 resin is a high density homopolymer with good barrier properties. The grade offers high stiffness, high temperature resistance and relatively high grease resistance. The resin has a low gel level.

SABIC® HDPE PCGF0863 is typically used for flexible packaging, pharmaceuticals and devices and release liners.

Film properties have been measured at cast film of 25 µm. Water vapor permeability at 38 °C and 100 % RH per 24 h. Oxygen permeability at 23 °C and 0 % RH per 24 h.

Compliance to regulations.

SABIC® HDPE PCGF0863 complies with the relevant monographs of the European Pharmacopoeia (EP) and the United States Pharmacopoeia (USPVI).

TYPICAL PROPERTY VALUES

Revision 20191018

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Melt Flow Rate (MFR)			
at 190 °C and 2.16 kg	8	dg/min	ISO 1133
Density	964	kg/m³	ISO 1183
FILM PROPERTIES			
Tensile test film			
Yield stress TD	24	MPa	ISO 527-3
Yield stress MD	26	MPa	ISO 527-3
Stress at break TD	18	MPa	ISO 527-3
Stress at break MD	22	MPa	ISO 527-3
Strain at break TD	800	%	ISO 527-3
Strain at break MD	700	%	ISO 527-3
Modulus of elasticity TD	580	MPa	ISO 527-3
Modulus of elasticity MD	580	MPa	ISO 527-3
Permeability			
water vapour (H ₂ O)	4.0	g/m²day	SABIC method
oxygen (O ₂)	0.1	ml/m²day	SABIC method
THERMAL PROPERTIES			
DSC test			
melting point	134	°C	DIN 53765
enthalpy change	224	J/g	DIN 53765

ENVIRONMENT AND RECYCLING

The environmental aspects of any packaging material do not only imply waste issues but have to be considered in relation with the use of natural resources, the preservations of foodstuffs, etc. SABIC considers polyethylene to be an environmentally efficient packaging material. Its low specific energy consumption and insignificant emissions to air and water designate polyethylene as the ecological alternative in comparison with the traditional packaging materials. Recycling of packaging materials is supported by SABIC whenever ecological and social benefits are achieved and where a social infrastructure for selective collecting and sorting of packaging is fostered. Whenever 'thermal' recycling of packaging (i.e. incineration with energy recovery) is carried out, polyethylene -with its fairly simple molecular structure and low amount of additives- is considered to be a trouble-free fuel.

© 2024 Copyright by SABIC. All rights reserved

CHEMISTRY THAT MATTERS™



STORAGE AND HANDLING

Polyethylenes resins (in pelletised or powder form) should be stored in such a way that it prevents exposure to direct sunlight and/or heat, as this may lead to quality deterioration. The storage location should also be dry, dust free and the ambient temperature should not exceed 50 °C. Not complying with these precautionary measures can lead to a degradation of the product which can result in colour changes, bad smell and inadequate product performance. It is also advisable to process polyethylene resins (in pelletised or powder form) within 6 months after delivery, this because also excessive aging of polyethylene can lead to a deterioration in quality.

DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NON-INFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.

PETROMALL

