



VinPol™ LD12515

Low Density Polyethylene

Melt Index: 12.5

Density: 0.915

VINPOL LD12515 is an autoclave LDPE extrusion coating grade resin designed for high speed coating applications with good drawdown. The high melt index and lower density of this resin allows for good seals at low temperatures resulting in high packaging/sealing rates. This resin has paper and paperboard adhesion and provides a good moisture barrier. This resin is Kosher and FDA 21 CFR 177.1520 compliant.

*Resin Property	Typical Value	Units	Test Method
Melt Index, 2.16 Kg at 190°C	12.5	g/10 min	ASTM D-1238
Density	0.915	g/cm3	ASTM D-4883
Flexural Modulus, 2% Secant, 0.5 in/min (12.7 mm/min)	25,000 (172)	psi (MPa)	ASTM D-790
Tensile Stress at Break, 20 in/min (500 mm/min)	1,400 (9.7)	psi (MPa)	ASTM D-638, Type IV
Elongation at Break, 20 in/min (500 mm/min)	400	%	ASTM D-638, Type IV

**Unless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity*

Vinmar Polymers America cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties, but they should not be used to establish specification limits or used alone as the basis of design.

Vinmar Polymers America, LLC / 16825 Northchase Drive, Suite 1400, Houston, TX 77060
Phone: 281-902-0900 Fax: 281-260-8096

Rev. Date 09/18/2020

